

# Owner's Manual SPOOL TYPE WINCH

## **Used On The A3 and CX3 Volleyball Systems**

For set up video go to www.scheldesports.us and click on volleyball set up video. View the CX3 and A3 set ups which both use this winch.

### **GEN 2 WINCH**






### **Spool Type Winch Set-Up Instructions**

- 1. Unpack all materials and items.
- 2. To install, use a 10mm wrench to remove the 2 clamp bands, then place the winch onto one of the posts and reinstalling the clamp bands. The bottom of the winch box should be approximately 3 feet from the floor when the post is in the floor sleeve. The winch box should line up with the upper wheel. NOTE: Tighten the bolts securely so the winch does not slide when under tension.
- 3. Locate the top Kevlar cord on the net. Tie a loop on the end of the top cord. Put the cord over the top wheel then, place the loop onto the winch hook/finger. Tie this loop in a spot where most of the slack is out of the net and you can easily hook it up for subsequent set ups. See Illustration 1 for overhand loop knot that should be used here.
- 4. Flip the handle out then start cranking it to tighten the top of the net.
- 5. Once the top of the net is to the desired tightness simply fold the handle back down.
- 6. Do these steps in reverse to take down the net.

**ILLUSTRATION 1: OVERHAND LOOP KNOT** 



# Volleyball System Maintenance and Warranty Information

### Maintenance Instructions for Schelde Volleyball Equipment

- Make sure all nuts and bolts are tightened and secure.
- Lubricate the winch periodically with lithium grease by removing the 4 bolts that hold the winch on the post and placing grease on the gears. A dab of grease will do. Rotate the handle to distribute the grease evenly on the gears.
- Padding can be cleaned with mild soap and water.
- Check cables for fraying and replace any with damage.
- Check T Handle lock for proper operation and locking. Replace if not locking properly.
- Replace warning labels and decals that are damaged. Contact Schelde Sports for new labels when needed.

Call Us! Whenever you have a question or concerns, we are here to serve you! (833) 724-3533

Schelde Sports North America recommends you inspect your systems a minimum of 2 times per year.

# Schelde Sports North America LLC warrants Schelde Sports brand Volleyball Systems to be free of all manufacturing defects as follows:

Upright tubing LIFETIME **Custom Base** 10 Years Linear Winch 10 Years Spool Type Winch 10 Years Floor Sleeve 10 Years **Brass Floor Plate** 5 Years Net 1 Year **Padding** 1 Year Connector Cable 1 Year Rail Hardware 1 Year Antennas 1 Year Sideline Markers 1 Year Referee Stand 3 Years Carts 3 Years

Defects caused by vandalism, abuse, neglect or lack of maintenance are excluded from warranty

Schelde Sports North America reserves the right to repair or replace at our sole discretion any defective item in the period listed above which begins when material is shipped from our warehouse

#### CUSTOMER IS RESPONSIBLE FOR ALL SHIPPING CHARGES FOR WARRANTY ITEMS.

THE WARRANTY DOES NOT COVER, AND IS INTENDED TO EXCLUDE, ANY LIABILITY ON THE PART OF SCHELDE SPORTS NORTH AMERICA LLC, WHETHER UNDER THIS WARRANTY OR UNDER ANY WARRANTY IMPLIED BY LAW, FOR ANY INDIRECT OR CONSEQUENTIAL CAMAGE FOR BREACH HEREOF OR THEREOF.

Note: Some states do not allow limitation on how long an implied warranty lasts or on the exclusion of indirect or consequential damages, so the above limitation on the duration of implied warranties and the above exclusions of incidental and consequential damages may not apply to you.

### Schelde Sports North America

2119 Old US 27 S Ste. C

ST Johns MI 48879

Ph: 833-724-3533 F: 517-999-8245

E-Mail: info@scheldesports.com Website: www.scheldesports.us